





TECHNICAL SPECIFICATIONS

.....100% Polypropylene Material

Grey (Virgin) Colour ...

Grid Weight 2.5 lbs (1.13 kg)

Cell Shape Honeycomb

Cell Wall Thickness 0.09" (2.3mm)

Crush Resistance (unfilled) ------>30,700 lbs/ft² (Over 150 tons/m²)

Load Bearing Capacity (Filled) ------ >46,451 lbs/ft² (Over 250 tons/m²)

Chemical Resistance Excellent

UV Resistance ----- Excellent

Suggested Aggregate Size ----- 0.2" - 0.6" (5-15mm)

CERTIFICATES/COMPLIANTS

LEED: Used in SUDS and LEED Compliant Porous

SGS: ASTM D1621-04A (compressive test standard)

ADA Compliant: Used in ADA Disability Compliant Surfaces for Pedestrians, Biycles, & Wheelchair Traffic

Environmentally Approved: Maryland Department of the Environment, Montgomery County, and City of Victoria, British Columbia

FEATURES





Stake holes for additional stability

Easy DIY Connectors

SUITABLE FOR

Residential Low-slope driveways, Parking Areas, Patios/Pathways, Access Lanes.









info@corelandscapeproducts.ca



2750 Cumberland Rd, Courtenay, BC



shop.coregravel.ca



+1 855 777 2673